

Conductivity Meter CM 35+

- Ergonomic and robust instrument, IP 67 Waterproof, resistant to harsh working conditions
- Automatic calibration in 1,2 or 3 points selected
- KIT version are available that include carrying case, accessories and sensor
- The carrying case include all necessary accessories to ensure accurate measurement.
- With built in Pt-1000 temperature sensor
- Conductivity calibration with 1, 2 or 3 standards selectable between 147µS/cm, 1413µS/cm, 12.88 mS/cm and 111.8 m/Scm (at 25°C)
- With liquid crystal, backlit with pictograms display
- Operating Temperature: 0°C to 50°C
- Storage temperature: -15°C to 65°C
- 80% relative humidity (non-condensing)



Specification of Conductivity Meter CM 35+

Model	CM 35+
Conductivity Testing Range	-0.01 µS/cm...500 mS/cm
Salinity Range	0.0...1999 mg/l NaCl, 2.0--50.0 g/l NaCl
TDS Range	0 mg/l...500 g/l
Temperature Range	-20.0...150.0°C
Reproducibility	Conductivity ±0.1% Salinity ±0.1% TDS: ±0.1% Temperature: ±0.1°C
Measuring Error	Conductivity ≤0.5% Salinity: ≤0.5% TDS: ≤0.5% Temperature: ≤0.2°C
Reference Temperature	20 or 25°C
Temperature Coefficient	0.00 a 9.99%/°C
Power Supply	3 x 1.5V, AA Batteries, Autonomy of over 400 hours
Material	ABS, Degree of Protection IP 67
Weight	300g, Size: 186 x 73 x 38mm

Oxygen Meter OXI 45+

- Ergonomic and robust instrument, IP 67 Waterproof, resistant to harsh working conditions
- OXI 45+ has a large LCD display with icons and backlighting, with easy to read
- Two measuring modes: in continuous or by stability. Calibration in 1 or 2 points
- Material ABS, Degree of protection IP 67
- The display by liquid crystal, backlit with pictograms
- Operating Temperature: 0°C to 50°C
- Storage temperature: -15°C to 65°C
- 80% relative humidity (non-condensing)
- According to CE, UNE-EN 61010-1 and UNE-EN 61326-1



Specification of Oxygen Meter OXI 45+

Model	OXI 45+
Saturation Range	0.0 to 199.9% and 200 to 250% (25°C)
Concentration Range	0.00 to 19.99 mg/l and 20.0 to 22.0 mg/l (25°C)
Reproducibility	Dissolved oxygen: ≤0.5 temperature: ≤0.2°C
Temperature	0.0 to 50.0°C
Measurement Error	Dissolved oxygen: ≤0.5 temperature: ≤0.2°C
Calibration	1 or 2 points 0% and 100% of saturation. Manual Calibration
Connector	MP-5, 5 contact multipin
Power Supply	3 x 1.5V, AA Batteries, Autonomy of over 500 hours
Material	ABS, Degree of Protection IP 67
Weight	300g, 186 x 73 x 38mm