

Refrigerated Incubator

- Interior of incubator is made of stainless steel, and exterior is made of quality steel.
- Microprocessor PID temperature controller with temperature control protection, digital display and timing function ensures a precise reliable temperature control.
- Independent alarm system for over temperature.
- With glass window for observation.



Specification of Refrigerated Incubator

Model	ST-70C	ST-150C	ST-250C	ST-500C	ST-800C	ST-1000C
Capacity	70L	148L	250L	500L	800L	1000L
Interior Dimension (mm)	400 x 350 x 500	500 x 470 x 808	540 x 460 x 1000	800 x 700 x 900	965 x 580 x 1430	900 x 580 x 1600
Exterior Dimension (mm)	530 x 560 x 1080	600 x 630 x 1360	637 x 662 x 1590	1000 x 1100 x 1860	1475 x 890 x 1780	1410 x 890 x 1950
Shelves	2 PCS	3 PCS	3 PCS	3 PCS	3 PCS	3 PCS
Timer	1-9999 minutes					
Temperature Range	4 ~ 60°C					
Temperature Precision	0.1°C					
Temperature Stability	± 0.5°C					
Ambient Temperature	+5 ~ 35°C					
Power	350W	450W	680W	1500W	1800W	2000W
Electrical Requirement	AC 220V 50/60Hz					

Environmental Testing Incubator

- Interior of incubator is made of stainless steel, and exterior is made of quality steel.
- Microprocessor PID temperature controller with temperature control protection, digital display and timing function ensures a precise reliable temperature control.
- Independent alarm system for over temperature.
- With glass window for observation.



Specification of Environmental Testing Incubator

Model	ST-150H	ST-250H
Capacity	148L	270L
Interior Dimension (mm)	500 x 370 x 800	550 x 445 x 1100
Exterior Dimension (mm)	600 x 620 x 1465	620 x 690 x 1750
Shelves Per Chamber	3 (PCS)	4 (PCS)
Timer	0-9999 minutes	
Temperature Range	4 ~ 80°C	
Temperature Precision	0.1°C	
Temperature Stability	± 0.5°C	
Ambient Temperature	+5 ~ 35°C	
Humidity Range	55-95% RH (at 20 ~ 45°C)	
Humidity Stability	± 5% RH	
Input Power	500W	680W
Net Weight	100 kg	150 kg
Electrical Requirement	AC 220V 50/60Hz	