

Autoclave Type B, Table Top Model

- Complies with the following:
93/42/CEE
97/23/CEE
EN13060:2004
EN610610-1
EN910940-2-041
- The new design model with opening water tank on the top, strictly comply to EN 1301
- Three-times pre-vacuum preceding vacuum drying.
- Vacuum up to 0.8 bar.
- The steam passes through fabrics, hollow equipment and pack of instrument.
- Sterilization temperature up to 135°C.
- Pre-programmes for sterilizing unwrapped instruments, cotton yarn, package of instruments, plastic or rubber.
- All-round computerized fuzzy control, digital display of working parameters.
- Installed with BOWIC & DICK which measures the penetration of steam.
- Mini printer can be attached to record the process of sterilization.
- Model ST-IID - same as ST-IIC but with mini printer, LCD display.
- Model ST-IID+ - same as ST-IIC but without printer, LCD display, curve progress display and USB port.



Specification of Autoclave Type B, Table Top Model

Model	ST-IIC12	ST-IIC18	ST-IIC23
Capacity	12L	18L	23L
Chamber Dimension (mm)	192 x 340	245 x 340	245 x 470
Exterior Dimension (W x H x D) mm	435 x 606 x 392	435 x 606 x 392	435 x 716 x 392
Weight	44kg	47kg	53kg
Power	1400W	1500W	1700W
Power Supply		220V	

Accessories:



Water Distiller, Model: ST-WD

- Water distiller, benchtop, no inlet connection, stainless steel interior.
- For use with autoclaves, supply with discharge container 4L.
- Output: 1.5L/ hour.
- Distiller capacity: 4L
- External dimension: 280 x 230 x 380mm
- Weight: 4kg
- Power: 220V/ 50Hz, 700W



Bag Sealer, Model: ST-BS250

- For polypropylene and polyester bag with paper base.
- Stainless steel tray and corrosion-proof outer parts.
- Adjustable sealing temperature from 180 ~ 200°C.
- Bag size up to 250mm, sealing width to 10mm.
- External dimension: 430 x 340 x 250mm.
- Weight: 6kg.
- Power: 220V/ 50Hz, 500W.

Accessories:

Polypropylene Bag	
ST-BS0502	50mm x 200m
ST-BS0752	75mm x 200m
ST-BS1002	100mm x 200m
ST-BS1502	150mm x 200m
ST-BS2002	200mm x 200m
ST-BS2502	250mm x 200m