

6-Position Heating Mantle

- Used in laboratory research, factories, scientific research institution.
- The product is reliable, simple, whole rational structure, has a continuously adjustable heating power.
- Heating power shown is easy to observe, control the heating, continuously adjustable to adapt to different needs.
- Sheet metal covered with chemical resistant epoxy paint finishing.
- Individually controlled heating power with on/ off switch, indicator lights and meter display of power.
- Supplied with support rod, bosshead and clamps.



Specification of 6-Position Heating Mantle

Model	ST-XL06-100	ST-XL06-250	ST-XL06-500	ST-XL06-1L	ST-XL06-2L
Capacity	100ml	250ml	500ml	1000ml	2000ml
Maximum Temperature	450°C				
Operating Criteria	High heating up to 4-8 hours				
	Lower heating up to 24 hours				
Power	70W	150W	200W	350W	450W
Voltage	220V 50Hz				

Digital Heating Mantle

- Case made of cold-rolling steel with surface of spray.
- Temperature-set, automatic control large heating area, quick heating-up, high evenness and time-saving.
- Anti-corrosive ageing-resistant and long durability.
- Beautifully shaped, simple-operating.
- Reserve adjustable tube-sketch.
- Supply complete with support rod and temperature probe.



Specification of Digital Heating Mantle

Model	ST-HMD50	ST-HMD100	ST-HMD250	ST-HMD500	ST-HMD1000	ST-HMD2000	ST-HMD3000	ST-HMD5000	ST-HMD10000	ST-HMD20000
Capacity (mL)	50	100	250	500	1000	2000	3000	5000	10000	20000
Maximum Temperature (°C)	0 ~ 380°C									
Heating Power	80W	100W	150W	250W	350W	450W	600W	800W	1200W	2500W
Working Time	Continuous									
Overall Dimension (mm)	Ø 220 x 165			Ø 280 x 220	Ø 330 x 230	Ø 340 x 245	Ø 350 x 250	Ø 425 x 320	550 x 510 x 390	
Weight	2.5kg			5.5kg	6.5kg	7.5kg	8.5kg	9.8kg	21kg	
Power	220V									

Heating Mantle

- Case made of cold-rolling steel with surface of spray.
- Electronic control, large heating area quick heating-up, high evenness.
- Anti-corrosive and long durability.
- Beautifully shaped, simple-operating.



Specification of Heating Mantle

Model	ST-HM50	ST-HM100	ST-HM250	ST-HM500	ST-HM1000	ST-HM2000	ST-HM3000	ST-HM5000	ST-HM10000	ST-HM20000
Capacity (mL)	50	100	250	500	1000	2000	3000	5000	10000	20000
Maximum Temperature (°C)	0 ~ 380°C									
Heating Power	80W	100W	150W	250W	350W	450W	600W	800W	1200W	2500W
Working Time	Continuous									
Overall Dimension (mm)	Ø 220 x 165			Ø 280 x 220	Ø 330 x 230	Ø 340 x 245	Ø 350 x 250	Ø 425 x 320	550 x 510 x 390	
Weight	2kg			3.5kg	4kg	6kg	7kg	10kg	21kg	
Power	220V									