



# Magnetic Stirrers “Agimatic-ED” and “Agimatic-ED-C” digital control

FOR SPEEDS FROM 60 TO 1600 RPM.  
FOR ADJUSTABLE TEMPERATURES FROM 50 °C TO 350 °C. PRECISION  $\pm 2$  °C.  
MAXIMUM STIR VOLUME: 10 LITRES.  
PLATE Ø IS 14,5 cm.  
WITH REMOVABLE SAFETY RING AGAINST SPILLAGES.



## “Agimatic-ED” with heating

ELECTRONIC TEMPERATURE CONTROL OF SPEED AND POWER TO THE HEATER.  
SILUMIN UPPER PLATE COVERED BY AISI 304 STAINLESS STEEL.

### CONTROL PANEL

1. Digital display indicating stir speed or temperature.
2. Push button, parameter selector, Stir speed or Temperature.
3. Push button, increase parameter value.
4. Push button, decrease parameter value.
5. Indicator lamp, safety thermostat “on”
6. Push button Stop-Start

Precision  $\pm 2$  °C.

Part No. **7001511**

Supplied with a PTFE coated stir bar of  $\varnothing 8 \times 40$  mm. long.



Connection at the back to connect:

Electronic contact thermometer “Sensoterm II”



Electronic temperature regulator “Electemp”



Temperature sensor Pt100



## “Agimatic-ED-C” with heating

ELECTRONIC TEMPERATURE CONTROL OF SPEED AND POWER TO THE HEATER.

SILUMIN UPPER PLATE WITH CERAMIC SURFACE.

### Ceramic surface:

Excellent conductivity and heat distribution.  
Unalterable surface.  
Higher acceleration to reach temperature.  
Extreme resistance against chemical agents and scratches.



### CONTROL PANEL

1. Digital display indicating stir speed or temperature.
2. Push button, parameter selector, Stir speed or Temperature.
3. Push button, increase parameter value.
4. Push button, decrease parameter value.
5. Indicator lamp, safety thermostat “on”
6. Push button Stop-Start

Precision  $\pm 2$  °C.

Part No. **7001609**

Supplied with a PTFE coated stir bar of  $\varnothing 8 \times 40$  mm long.



Connection at the back to connect:

Electronic contact thermometer “Sensoterm II”



Electronic temperature regulator “Electemp”



Temperature sensor Pt100



Complements for Agimatic-ED and Agimatic ED-C. See accessories on pages 34 and 35.