



Digital bacteriological incubators "Incudigit"

NATURAL CONVECTION.
 DIGITAL CONTROL AND DISPLAY OF TEMPERATURE AND TIME.
 ADJUSTABLE TEMPERATURE FROM AMBIENT +5 °C UP TO 80 °C.
 STABILITY: ± 0.1 °C, UP TO 37 °C. HOMOGENEITY: ± 0.5 °C, UP TO 37 °C.
 SET ERROR: $\pm 2\%$ OF THE WORKING TEMPERATURE, RESOLUTION 0.1 °C
 INTERNAL TEMPERED GLASS DOOR.




FEATURES, CONTROL PANEL, STANDARD AND ACCESSORIES (see pages 134 and 135).

SAFETY:
 OVER TEMPERATURE CUT OUT INCORPORATED ACCORDING TO THE EN.61010 STANDARD.
 ADJUSTABLE SAFETY THERMOSTAT DIN 12880.3.1 FITTED.



Horizontal model. Part No. 2001616



Performance graph of temperature and time.

A. Set at 80 °C: 1 h 12'

B. Set at 56 °C: 54'

C. Set at 37 °C: 48'

RS-232 Interface output for a computer, printer or USB adapter.

STANDARD EQUIPMENT

2 shelves and 4 shelf guides.

MODELS

Part No.	Capacity litres	Height / Width / Depth (interior) cm	Height / Width / Depth (exterior) cm	Shelves positions	Power W	Weight Kg
2001246	19	30 25 25	50 60 44	5	150	26
2001247	36	40 30 30	60 65 49	7	225	36
2001616	52	33 47 33	53 82 52	5	250	46
2001248	80	50 40 40	70 74 59	8	300	54
2001249	150	50 60 50	70 95 68	8	525	75

SPARES

Shelves and guides.

Oven Part No.	2001246	2001247	2001616	2001248	2001249
Guides (2) (Set)	2000011	2000012	2000012	2000013	2000015
Shelves	2000021	2000022	2000024	2000023	2000025

Each self requires two guides i.e. one set.

ACCESSORIES



4120131 USB adapter model.

Pen-Drive included (Memory board) for data storage.

Accessories must be factory installed.



2000016 Digital printer for time and temperature with numerical printout on continuous paper roll, with print intervals from 1 minute to 99 hours.



OVENS AND INCUBATORS SERIES 2000

MODELS:

- NATURAL AIR CONVECTION, DRYING AND STERILIZATION.
- FAN ASSISTED CIRCULATION, UNIVERSAL APPLICATIONS.
- NATURAL AIR CONVECTION, BACTERIOLOGY AND INCUBATION.

CONTROL: ANALOGUE OR DIGITAL MICROPROCESSOR CONTROL OF TEMPERATURE AND TIME, MODEL DEPENDENT.
COMPLIES WITH THE STANDARDS: DIN 50011 - DIN 58945. REQUIRED FOR HEATING, STABILITY AND HOMOGENEITY.

2000
serie

SAFETY:

STANDARD EN.61010. INCORPORATED FIXED OVER TEMPERATURE DEVICE .
STANDARD DIN 12880.2. (CLASS 2 AND 3.1)SAFETY THERMOSTAT CONTROLLER FITTED.

Leading edge technology



ORIGINAL SELECTA

Locking device on analogue temperature controls and security.



Detailed longitudinal cross section.

COMMON FEATURES

Construction.

1. External case treated with a corrosive resistant epoxy coating.
2. Internal part: Easy to clean AISI 304 stainless steel double chamber, self adjusting door seal and adjustable shelves and guides.
3. Control panel: independent insulated control panel to facilitate all types of instruments, controls and regulators.
4. Adjustable air inlet.
5. Flexible floating door seal, self adjusting that maintains the best possible seal.

Technical Properties.

6. Excellent thermal qualities of the insulation has the optimum performance according to heater capacity and power consumption, with minimal external temperature loss.

7. Independent heating chamber for the heating elements to obtain an even heat distribution and rapid temperature equilibrium and stabilization.

Fan assisted convection models have a turbo fan. All incubators for bacteriology and cell culture have a second inner door of tempered glass.

Technology from J. P. Selecta:

8. Locking device in analogue temperature controls.
9. Adjustable guide and shelf positions.
10. Double seal around the chamber to provide a gentle but effective seal.
11. Floating spring door that adjusts the pressure and absorbs the thermal expansion.
12. Adjustable door pressure system closure.


NOTE:

For all models, the values for stability and homogeneity shown are based on temperature conditions with the ventilation closed. The optimum homogenization of temperature within the chamber is based on a reasonable load that does not surpass more than 70 % of the volume of the chamber. The graphic results shown for temperature for each model are based on the above criteria.

CONTROL PANELS


Models with Analogue control.

1. Mains switch.
2. "On" indicator lamp.
3. Temperature control thermostat.
4. Heating "ON" indicator lamp.
5. Analogue thermometer temperature indicator.
6. Vacant positions for additional accessories.
7. Controllable safety thermostat that disconnects power to the heater in case of a fault in the main thermostat, manual reset (Directive DIN12880.2 class 2 and 3.1) and function signal lamp.



Models with microprocessor control and digital display.

1. Mains switch with "ON" indicator.
2. Temperature mode indicator.
3. Time mode indicator.
4. Display for temperature and time.
5. Operating, "RUN" mode.
6. Delay time state indicator.
7. Push button temperature selector.
8. Push button time selector.
9. Push button "increase" value or parameter.
10. Push button "decrease" value or parameter.
11. Push button Start / Stop.
12. Set temperature.
13. Set run time: time period from 1 minute to 9 hours 59 minutes, or up to 99.9 hours, once the set temperature value has been reached.
14. Set wait time before starting the run, time period from: 1 to 24 hours.
15. RS-232 Interface output for a computer, printer or USB adapter.
16. Controllable safety thermostat (that disconnects power to the heater in case of a fault in microprocessor), manual reset and function signal lamp.



MODEL SUMMARY TABLE

Models	CONTERM	DIGITHEAT	DIGITRONIC	INCUBAT	INCUDIGIT
TYPE	Drying Oven	Drying Oven	Universal	Bacteriological Incubator	Bacteriological Incubator
CONTROL	Temperature	Temperature + time	Temperature + time	Temperature	Temperature + time
DISPLAY	Analogue	Digital	Digital	Analogue	Digital
AIR	Convection	Convection	Fan assisted	Convection	Convection
CIRCULATION	natural	natural		natural	natural
CAPACITY LITRES	19 - 36 - 52 - 80 - 150	19 - 36 - 52 - 80 - 150	33 - 47 - 76 - 145	19 - 36 - 52 - 80 - 150	19 - 36 - 52 - 80 - 150

ACCESSORIES



Part No.
2000002 Timer switch 0-120 minutes.
Suitable for **CONTERM**.

2000003 Timer switch 0-12 hours.
Suitable for **CONTERM** and **INCUBAT**.

2000009 24 hour programmer with continuous on/off cycling up to every 15 minutes.
Suitable for **CONTERM** and **INCUBAT**.



4120131 USB adapter model.
Pen-Drive included (Memory board) for data storage. Only for RS-232 outlet ovens.



Part No.
2000016 Digital printer for time and temperature with numerical printout on continuous paper roll, with print intervals from 1 minute to 99 hours.
Suitable for **DIGITHEAT**, **DIGITRONIC** and **INCUDIGIT**.



2000007 Digital programmable microprocessor.
Capacity: 10 programs of 100 segments. Programmable timer: up to 99 hours 59' 59". Program repetition: up to 99 times. Programs can also be linked for up to 4 stages. RS-232 interface for data down load to a printer or computer.
Suitable for **DIGITRONIC**.