

## Upright Low Temperature Freezer (-25°C to -40°C)



- This Upright Low Temperature Freezer is the specific medicine cold-storage equipment. it can be also used for storing reagent, vaccine, biological, etc. especially for hospital, pharmacy, pharmaceutical factory, epidemic station, blood bank station, health center and laboratory.

- **Precise temperature control system**

The high-accuracy microcomputer-controlled temperature system maintains the temperature at -10~ -25°C precisely. The temperature set-value can be adjusted from -10°C ~ -25°C, and the temperature display precision is 0.1°C, the resolution is 0.1°C and the adjusting increment is 0.1°C. The value is to be displayed through three-digital high-brightness figure. The system has special high-resolution temperature calibrating function. That means the set-value figure can be displayed and calibrated at -10°C ~ -25°C. The calibrating increment is 0.1°C. The forced cold-air circulation system ensure the temperature uniformity inside the chamber.

- **Control System**

Keyboard lock, password protection function, to prevent unauthorized adjustment of the operating parameter; setting of the alarm temperature range. 7 system failure alarms (high temperature alarm, low temperature alarm, sensors failure alarm, door-opening alarm, electricity failure alarm, low back-up battery alarm, low voltage alarm). Standard alarm for high/low temperature and sensor failure. Code display of the failure position (some machines have all these seven alarms); The starting delay function due to self-checking and the interval protection function between temporary stop and start will ensure the reliable operation; The system can record the condition of the maximum and the minimum temperature inside the box automatically without recording paper. With the specially designed function, the system can operate under the state of sensor failure or the state of numerical disturbance safely and automatically. The operating parameter display function can ensure that the system is under supervision by operator and with security and stability. Equipped with remote alarm interface, The built-in lithium battery support the display of the chamber temperature and the alarm system for 72 hours after electricity failure.

- **Optional items :**

The EPS emergency supply is available, The DC24V-AC220V inverter is adoptable, and the DC24V power supply can keep the refrigerator under normal operation.

- **Refrigeration system**

Germany DANFOSS high-performance compressor;  
Original binding "Bi-Sonic" double fan strongly against the low temperature and moisture;  
Germany "EBM" heat elimination fan;  
Japanese Matsushita vaporizer (cooling pipeline inside the box);  
Fluoride-free refrigeration system for environmental protection.

- **Construction**

High quality adjustable plastic coated steel wire shelves.  
The large-screen design is easy for observation.  
Safety door lock.  
Wide voltage band for 187 — 242V voltage.  
The refrigerator body is made of high-quality structural steel plate, which is treated with advanced phosphate rust-proof spray coating.  
Double transparent insulation glazed door, filled with inert gas.  
The power saving lamps inside the freezer  
Internal made of ABS (Optional stainless steel available)

## Specification of Upright Low Temperature Freezer (-25°C)

Model	ST-UR25-120	ST-UR25-170	ST-UR25-200	ST-UR25-250	ST-UR25-300
Capacity (L)	120L	170L	200L	250L	300L
Weight (kg)	60	65	70	75	80
External Dimension (mm)	600 x 690 x 1550	600 x 690 x 1650	600 x 690 x 1750	600 x 690 x 1800	600 x 690 x 1820
Temperature (°C)	-10 ~ -25°C				
Voltage	220V 50Hz				

## Specification of Upright Low Temperature Freezer (-30°C)

Model	ST-UR30-120	ST-UR30-170	ST-UR30-200	ST-UR30-250	ST-UR30-300
Capacity (L)	120L	170L	200L	250L	300L
Weight (kg)	60	65	70	75	80
External Dimension (mm)	600 x 690 x 1550	600 x 690 x 1650	600 x 690 x 1750	600 x 690 x 1800	600 x 690 x 1820
Temperature (°C)	-10 ~ -30°C				
Voltage	220V 50Hz				

## Specification of Upright Low Temperature Freezer (-40°C)

Model	ST-UR40-120	ST-UR40-170	ST-UR40-200	ST-UR40-250	ST-UR40-300
Capacity (L)	120L	170L	200L	250L	300L
Weight (kg)	60	65	70	75	80
External Dimension (mm)	600 x 690 x 1550	600 x 690 x 1650	600 x 690 x 1750	600 x 690 x 1800	600 x 690 x 1820
Temperature (°C)	-10 ~ -40°C				
Voltage	220V 50Hz				